

Industrial Grade Shrink Wrappers

Proven technology from the market leader and innovator of the industry.



For almost 40 years, Minipack has provided a wide array of shrink wrap systems that meet the needs of all different types of operations, from the most compact manual systems to semi-automatic and fully automated systems, with advanced technology features. All systems are built with patented sealing technology and a powerful fan that ensures perfect packaging results. Intuitive controls and 10 user-settable programs allow for easy operation.



Sealing Technology

perfect sealing results

All machines are covered with a full view plexi-glass hood for easy operation. The teflon coated sealing blades hold up four times longer than conventional seal wire and are precisely temperature regulated.

Performance

powerful and reliable

With use of Polyolefin or PVC film, these machines can shrink wrap from 6-12 items per minute. The patented instant fan stop prevents heat dispersion and enables energy savings.

Display, Controls & Programmability

Intuitive control panels, ergonomically placed on the front of the machines with 3-digit display are clear and give complete information. 6-10 customizable programs increase operator productivity. Adjustable hood opening is based on product size. Programmable fan speed for selected systems available.











SMART TECHNOLOGY FEATURES

- Shrink wrap systems with film roll width of 20", 24", 32", and 40"
- Powerful fans with instant stop: patented system minimizes heat dispersion and create 20% energy savings when lid is opened
- Sensor controlled opening of lid according to height of product to be packaged (on selected product)
- Impulse heated sealing blade with electronic thermoregulation
- Tearless perforation system for films without proper perforation
- Performance cooling system: coolant fluid ensures precise temperature of seal blades
- Automatic waste film winder: for maximum workplace safety and efficiency
- Customizable programs from 6 to 10 to increase operator productivity
- Designed with easy access to all areas and parts of the machine



Six good reasons to choose minipack:

- » Focused on value and user-centered innovation
 - » Over 40 years track record as innovator
- » Reliability and cost advantage over the long run
 - » Committed to customer service and support
- » Certified quality manufacturing – ISO 9001:2000
- » Worldwide distribution network and technical assistance

Industrial Grade Shrink Wrappers		GALAXY	RP 40	RP 55	RP 55C	RP 55SA	RP 55A	RP 85	DIGIT 90
									
Sealing Area	Maximum Product Size (W x L x H)	17.00" x 14.00" x 8.00"	16.00" x 10.00" x 6.60"	20.00" x 16.00" x 8.00"	20.00" x 16.00" x 8.00"	20.00" x 16.00" x 8.00"	20.00" x 16.00" x 8.00"	32.00" x 20.00" x 8.00"	48.00" x 32.00" x 6.00"
	Center Folded Film Types	Polyolefin / PVC	Polyolefin / PVC	Polyolefin / PVC	Polyolefin / PVC	Polyolefin / PVC	Polyolefin / PVC	Polyolefin / PVC	Polyolefin / PVC
	Maximum Roll Width	20.00"	20.00"	24.00"	24.00"	24.00"	24.00"	32.00"	40.00"
	Maximum Roll Diameter	10.00"	10.00"	10.00"	10.00"	10.00"	10.00"	12.00"	10.00"
	Adjustable Product Height	✓	✓	✓	✓	✓	✓	✓	✓
	Automatic Lid Open	✓	✓	✓	✓	✓	✓	✓	✓
	Teflon Coated Sealing Blade	✓	✓	✓	✓	✓	✓	✓	✓
	Programmable Sealing Blade Temperature	✓	✓	✓	✓	✓	✓	✓	✓
Performance	Wraps per Minute*	up to 6 items	up to 6 items	up to 6 items	up to 8 items	up to 10 items	up to 12 items	up to 6 items	up to 4 items
	Heater Wattage	1700W	2100W	2800W	2800W	2800W	3400W	4200W	5300W
	Power Supply	115V / 18A	208V or 230V / 12A	208V or 230V / 16A	208V or 230V / 14A	208V / 3ph / 16A	208V / 3ph / 19A	208V / 3ph / 14A	208V / 3ph / 31A
Display & Controls	Water Resistant LED Display	✓	✓	✓	✓	✓	✓	✓	✓
	Digital Controls	✓	✓	✓	✓	✓	✓	✓	✓
	Customizable Programs	10	10	10	10	10	10	10	6
Operational Features	Machine Type	Manual	Manual	Manual	Semi-Automatic	Semi-Automatic	Automatic	Manual	Manual
	Automatic: Seal-Cut-Release	✓	✓	✓	✓	✓	✓	✓	✓
	Sealing Blade Heat	Impulse	Impulse	Impulse	Impulse	Impulse	Impulse	Impulse	Impulse
	3 Working Modes (Bag Only/Bag & Shrink/Multiples)	✓	✓	✓	✓	✓	✓	✓	✓
	Sealing Activation Modes: Timer/Push Button/Foot Pedal (optional)	-	-	-	✓	-	✓	-	-
	Auto-Discharge Conveyor	-	-	-	-	✓	✓	-	-
	Adjustable Hood Opening	✓	✓	✓	-	✓	-	✓	✓
	Programmable Conveyor Speed	-	-	-	-	✓	✓	-	-
	Programmable Fan Speed	-	-	-	✓	✓	✓	-	-
	Instant Fan Stop	-	-	-	✓	✓	✓	-	-
	Overheat Safety Circuit	✓	✓	✓	✓	✓	✓	✓	✓
	Programmable Sealing Arm Timer	-	-	-	✓	-	✓	-	-
	Precision Blade Cooling System	Air	-	-	Coolant Fluid	Coolant Fluid	Coolant Fluid	-	-
	Tearless Perforation System	✓	✓	✓	✓	✓	✓	✓	✓
	Patented Safety System	-	-	-	✓	-	✓	-	-
Lid Closure	Manual	Manual	Manual	Automatic	Manual	Automatic	Manual	Manual	
Service	Easy Frontal Access	✓	✓	✓	✓	✓	✓	✓	✓
	Indicating Display	✓	✓	✓	✓	✓	✓	✓	✓
	Error Codes	✓	✓	✓	✓	✓	✓	✓	✓
	1 Year Limited Warranty	✓	✓	✓	✓	✓	✓	✓	✓
Housing & Dimensions	Material	Fiberglass / Enameled	Steel / Baked Enamel	Steel / Baked Enamel	Steel / Baked Enamel	Steel / Baked Enamel	Steel / Baked Enamel	Steel / Baked Enamel	Steel / Baked Enamel
	Width x Length	41.00" x 28.00"	46.00" x 28.00"	50.00" x 32.00"	58.00" x 32.00"	58.00" x 32.00"	58.00" x 32.00"	78.00" x 40.00"	110.25" x 50.50"
	Height (Lid open/closed)	50.00" / 46.00"	50.00" / 46.00"	52.00" / 46.00"	52.00" / 46.00"	52.00" / 46.00"	52.00" / 46.00"	58.00" / 46.00"	52.00" / 46.00"
	Working Height	35.00"	36.00"	36.00"	36.00"	36.00"	36.00"	37.00"	35.00"
	Locking Casters	✓	✓	✓	✓	✓	✓	✓	✓
	Shipping Weight	201.4lbs	231lbs	264lbs	264lbs	389lbs	389lbs	530lbs	1113lbs
Optional Features	Taller Hood	Reverse Hood	-	✓	✓	✓	✓	✓	-
	Stainless Entry Plate	✓	✓	✓	✓	✓	✓	✓	✓
	Single Hole Punch	115V	115V	115V	-	-	-	-	-
	Foot Pedal	-	-	-	✓	-	✓	-	-
	Entry Film Opener	✓	✓	✓	✓	✓	✓	✓	-
	Automatic Waste Winder	✓	✓	✓	✓	✓	✓	✓	Standard
	Film Waste Ring	✓	-	-	-	-	-	-	-
	Product Guide	✓	✓	✓	-	-	-	-	-
	40" Film Roll Support	-	-	-	-	-	-	✓	-
Second Film Roll Kit	8.00" Diameter Roll	-	-	-	-	-	-	-	

Galaxy shown with optional automatic waste winder. *Depends on type of product, film and operator ability.

Specifications may change without notice.