

## 56 MPE Stainless Steel



### Downloads

- ▶ [Product Sheet \(pdf\)](#)

### Contact Us

- ▶ [Request a Quote](#)

Sealing Area	
Maximum Product Height	9.45"
Maximum Product Length	21.75"
Center Folded Film Types	Supports any film type
Maximum Roll Width	28"
Maximum Roll Diameter	12"
Adjustable Product Height	✓
Teflon Coated Sealing Blade	✓
Programmable Sealing Blade Temperature	✓
Performance	
Wraps per Minute*	30-50 items
External Pneumatic Seal Pressure Required	-
AC Servo Motor Driver	✓
Power Supply	230V / 1ph / 13A
Display & Controls	
Water Resistant Digital Display	Touch Screen
Control Board	PLC Schneider®
User-Settable Programs	Unlimited
Operational Features	
Machine Type	Automatic L-Sealer
Sealing Technology	Center Sealer
Motors	Non-pneumatic Servo Motors
Access	Two Gull-Wing Doors for Easy Access
Controls	Large Touch Screen Control Panel
Belt	Food-Approved Belting
Automatic: Seal»Cut»Release»Advance	✓
Sealing Blade Heat	Constant
Photo Cell Activation	✓
Auto-Entry Conveyor	✓
Auto-Discharge Conveyor	✓
Conveyor Belt Modes	Continuous / Step-Advance
Programmable Conveyor Speed	✓
Small Product Kissing Belt	✓
Overheat Safety Circuit	✓
Automatic Waste Winder	✓
No Moving Parts Exposed	✓
Tearless Perforation System	✓
Patented Safety System	✓
Service	
Easy Frontal Access	✓
Indicating Display	✓
Operating/Running/Problem Light	✓
Error Codes	✓
1 Year Limited Warranty	✓
Housing & Dimensions	
Material	Stainless Steel
Width x Length	97.75" x 49"
Height (Lid open/closed)	77" / 68"
Working Height	34"
Locking Casters	✓
Shipping Weight	1800lbs
Optional Features	
Sandwich Guide	✓
Single Hole Punch	✓
Belt Scraper	✓

\*Depends on type of product, film and operator ability. Specifications may change without notice.