

MV 1100 (Left & Right)



Chamber & Seal Bars	
Chamber Width x Length	45.50" x 35.75"
Chamber Height	11.00"
Number of Seal Bars (lid mounted)	2
Position of Seal Bars	Left & Right
Seal Bar Length	2 x 33.5"
Distance between Seal Bars	39.50"
Quick Change Seal Bars	✓
Independent Power to each Seal Bar	✓
Performance	
Pump Type	Busch R5 Oil Rotary
Cycles per Minute*	up to 3
Free Air Displacement @ 50Hz	300 m³/h
Free Air Displacement @ 60Hz	360 m³/h
Pump Power Rating	12 hp
Power Supply	220V / 3ph / 40A
Display & Controls	
Water Resistant Digital Display (IP65)	✓
Selectable Control (Time or %)	✓
Electronic Millibar Sensor	✓
Customizable Programs	9
Operational Features	
Programmable Sealbar Pre-Heat	✓
Programmable Sealing Time	✓
Gentle Air Return	✓
Gas Plus Program (pouch ballooning)	✓
Extra Vacuum (30 sec)	✓
Fast & Hygienic Lid Evacuation	✓
High Volume Density Plates	✓
Service	
Pump Conditioning	✓
Self Diagnostic	✓
Indicating Display	✓
Toolless Valve Replacement	✓
Programmable Service Reminder	✓
1 Year Limited Warranty	✓
2nd Year Conditional Warranty**	VP Program
Housing & Dimensions	
Material	Stainless 304
Lid Type / Lid Spring Alignment	Swing Lid / Horizontal
Width x Length	95.50" x 38.50"
Height (Lid open/closed)	63.25" / 46.00"
Working Height	33.00"
Locking Casters	✓
Shipping Weight	2128lbs
Optional Features	
Seal & Shrink Bag Cutter	✓
Gas Kit - N2/CO2/Ar	✓
Seal Bar Air Assist	✓

*Depends on type of product, film and operator ability.
 **Through a certified minipack america dealer.
 Specifications may change without notice.