

## MV 65X





### Downloads

▶ [Product Sheet \(pdf\)](#)

### Contact Us

▶ [Request a Quote](#)

Chamber & Seal Bars	
Chamber Width x Length	29" x 27"
Height (Chamber + Dome/Lid = Total)	5" + 5.5" = 10.5"
Number of Seal Bars	2
Position of Seal Bars	Left & Right
Seal Bar Length	2 x 26"
Distance between Seal Bars	24"
Seal: Flat (4mm) + Bag Trimmer	✓
Unique Waffle-Pattern Sealing	✓
Pop-Out Seal Bars	✓
Independent Power to each Seal Bar	✓
Performance	
Pump Type	Busch R5 Oil Rotary
Cycles per Minute*	up to 3
Free Air Displacement	63 m <sup>3</sup> /h
Pump Power Rating	3 hp
Power Supply	208V / 3ph / 19A
Display & Controls	
Water Resistant Digital Display	✓
LED Full Description Display	✓
Electronic Millibar Sensor	✓
Customizable Programs	9
Operational Features	
Programmable Sealing Time	✓
Programmable Vacuum Time (%)	✓
Moisture Quick Stop	✓
Excess Bag Cut-Off	✓
High Volume Density Plates	✓
Service	
Indicating Display	✓
Programmable Service Reminder	✓
1 Year Limited Warranty	✓
Housing & Dimensions	
Material	Stainless 304
Lid Type	Transparent with Dome
Width x Length	32" x 35"
Height (Lid open/closed)	58.25" / 41.25"
Working Height	35"
Locking Casters	✓
Shipping Wt.	580lbs
Certificates	
ETL Electrical	
ETL Sanitation (NSF Standard)	
Optional Seal Bars	
Liquid & Foil Bag Seal	✓
Optional Features	
Gas Kit (8 Nozzles)	✓
Gentle Air Return	✓
220V / 1ph / 22A / 63 m <sup>3</sup> /h	✓
208V / 3ph / 18A / 100 m <sup>3</sup> /h	✓

\*Depends on type of product, film and operator ability. Specifications may change without notice.