

Media



Downloads

- ▶ [Product Sheet \(pdf\)](#)

Contact Us

- ▶ [Request a Quote](#)

Sealing Area	
Sealing Area	22" x 16" x 9"
Center Folded Film Types	Polyolefin / PVC
Maximum Roll Width	24"
Maximum Roll Diameter	10"
Adjustable Product Height	✓
Programmable Seal Arm Opener	✓
Teflon Coated Sealing Blade	✓
Programmable Sealing Blade Temperature	✓
Performance	
Wraps per Minute*	12-16 items
External Pneumatic Seal Pressure Required	-
Heater Wattage	5700W (Tunnel)
Power Supply	200-240V / 3ph / 21A
Display & Controls	
Water Resistant Digital Display	LED
Digital Controls	✓
Customizable Programs	6
Operational Features	
Machine Type	Semi-Automatic
Automatic: Seal»Cut»Release	✓
Automatic: Seal»Cut»Release»Advance	✓
Sealing Blade Heat	Impulse
3 Working Modes (Bag Only/Bag & Shrink/Multiples)	✓
Auto-Discharge Conveyor	✓
Conveyor Belt Modes	Continuous / Step-Advance Continuous
Programmable Conveyor Speed	✓
Overheat Safety Circuit	✓
Precision Blade Cooling System	Coolant Fluid
Tearless Perforation System	✓
Stainless Entry Plate	✓
Double-Insulated Tunnel Walls	✓
18" Exit Roll Conveyor	✓
Sealing Activation Modes	Timer / Push Button / Foot Pedal
Patented Safety System	✓
Lid / Seal Arm Closure	Automatic
Electric Scrap Winder	✓
Service	
Easy Frontal Access	✓
Indicating Display	✓
Error Codes	✓
1 Year Limited Warranty	✓
Housing & Dimensions	
Material	Steel / Baked Enamel
Width x Length	91" x 28.5"
Height (Lid open/closed)	54.5" / 34.5"
Working Height	32"
Locking Casters	✓
Shipping Weight	755lbs
Optional Features	
Single Hole Punch	115V
Film Entry Extension	✓
Foot Pedal	✓
Teflon Belt (for Tunnel)	✓

*Depends on type of product, film and operator ability.
 Specifications may change without notice.